

RADIATOR THERMOSTAT PANEL

PTR

cod. 6100-135000



* Civil series › p. 97



It allows the guest to change temperature, switch on and off the heating.

The display shows time and set and measured temperature. The light sensor optimises contrast and luminous symbols give information on operation status. It is housed in 3-module box and connected to the control unit by means of 6-wire cable terminated with RJ12 PLUG.

Weight: 0.10 kg. Depth 45mm.

AMPLIFIED POWER SUPPLY

A20 / 5

cod. 3200-211010



The preamplification circuit is provided with one Aux input for connection of an external sound source (CD player, etc.), and one input to process the signal from max. 3 desktop microphone units BMCP/A for priority call on sound source. It is also provided with adjustment of input level of the Aux and Mic signals and with adjustment of output signal level, suitable for connection with lines of "SM" series amplified speakers. It can power max. n. 20x10W or n. 5x20W powered speakers. For installations with a higher number of speakers additional A20/5 power supplies must be used. Made of painted metal, for wall-mounted or desktop installation.

TECHNICAL SPECIFICATIONS

Input impedance Aux	100K Ω
Input sensitivity Aux	-12dB
Input impedance Mic.	15 K Ω
Output sensitivity	10 Ω
Max output level	+8dB -4Vpp
Power supply	220Vac
Power absorption	120VA
Distributed voltages	18Vdc/4A - 12Vdc/1A - 9Vdc/0,5A
Dimensions	230x60x210mm
Material	metal
Colour	black
Weight	3,6kg