ADDITIONAL POWER SUPPLY

PREAMPLIFIED DESKTOP MICROPHONE UNIT

AS20 / 5

cod. 3100-131010



BMCP / A

cod. 3200-221010







In amplified systems it enables power supply for n. 20x10W or n. 5x20W powered speakers of the 'AUDIO RSA' series. Produced in painted metal, it can be wall mounted or supported on a surface.

Unit with gooseneck microphone, cardioid electret with luminous ring, suitable for voice announcements in combination with A20/5 or AD20/5 power supply.

It can be also connected to announcement generator GSV. Provided with one stable and one unstable button to activate microphone and priority contact for attenuation of sound source connected to the same power supply, and activate the circuit to generate the dual-tone signal. Two leds indicate button activation.

It is powered directly from the power supply to which it is connected. Aluminium extruded body, ABS sides with feet. Complete with 5m connection cable. Grey/ black colour.

TECHNICAL SPECIFICATIONS

 Power supply
 220Vac

 Power absorption
 120VA

 Distributed voltage
 18Vdc/4A

 Dimensions
 230x60x210mm

 Material
 metal

 Colour
 black

 Weight
 3,4Kg

TECHNICAL SPECIFICATIONS

Output impedance 10KO Output level 3Vpp 100÷15000Hz Frequency response Power supply 12Vdc 50mA electret - 500mm rod Microphone type Dimensions 206x550x130mm Material plastic/metal Colour black/grev Weight 1,4Kg

GRMS | ITC 73 MEGA RSA