20W CEILING-MOUNT SPEAKER

20W CEILING-MOUNT SPEAKER

20W CEILING-MOUNT SPEAKER

DCP2017 / P

B cod. 4300-241201 N cod. 4300-241202 G cod. 4300-241203 DC20 / P

cod. 4300-120201

DC23 / P

cod. 4300-123201




















Passive ceiling rectangular mount speaker, with rounded angles, for excellent playback quality of voice announcements and background music in applications that require high-fidelity sound. ABS body with painted metal grille, provided with rotary hooks for easy and quick installation in false ceilings. Alternatively, it can be wall mounted with the GEWISS PT5 box (not included). Available in: white, black and grey.

Passive ceiling rounded mount speaker for excellent playback quality of voice announcements and background music. Painted metal body and grille, provided with rotary hooks for easy and quick installation in false ceilings.

Passive ceiling rounded mount speaker for excellent playback quality of voice announcements and background music in applications that require high-fidelity sound. Painted metal body and grille, provided with rotary hooks for easy and quick installation in false ceilings.

TECHNICAL SPECIFICATIONS

recessed in false ceiling Type RMS power 20W 120 ÷ 18000Hz Frequency response S.P.L. 1W@1m 93dB 4" Bicone Speaker type Speaker impedance 40 Dimensions 195x166x55mm Hole dimensions 155x125mm ABS/steel Material Colour white, black, grey 0,9Kg Weight

TECHNICAL SPECIFICATIONS

recessed in false ceiling 20W RMS power 110 ÷ 15000Hz Frequency response S.P.L. 1W@1m 90 ±3dB 5" full range Speaker type Speaker impedance 80 Dimensions ø 200mm x 50mm Hole dimensions ø 170mm Material steel Colour white Weight 0,7Kg

TECHNICAL SPECIFICATIONS

recessed in false ceiling Type RMS power 20W 90 ÷ 18000Hz Frequency response S.P.L. 1W@1m 91 ±3dB 6" full range Speaker type Speaker impedance 80 Dimensions ø230mm x 106mm Hole dimensions ø200mm Material steel Colour white 1,2Kg Weight