

2IN-2OUT EXPANSION UNIT

UE2-IP

cod. 6700-109020



The 2IN-2OUT expansion unit is housed in a 3-module box for DIN rail. It has two configurable analog inputs which, when combined with the UGC-IP room control unit, can be connected to the following devices:

- bathroom temperature sensor;
- room temperature sensor;
- bathroom window switch;
- room window switch;
- open shutters button
- close shutters button.

If used with the UGT-IP technological control unit, may be connected to:

- temperature sensors for common areas;
- alarm or anomaly contacts;
- switches;
- buttons;
- bathroom emergency pull cords;
- overflow sensors;
- energy meters.

It also has four relay outputs with voltage-free contacts for 230Vac, 4(2)A loads for managing devices connected to the relative inputs (thermostats, shutters, etc.) and ON/OFF or timed activation via computer. Connection to UGC-IP or UGT-IP control unit and other expansion and monitoring units via RJ12 connectors also with necessary 12Vdc power supply. Dimensions 52x100x62 mm. Weight 0.1 Kg.

4IN-4OUT EXPANSION UNIT

UE4-IP

cod. 6700-109040



The 4IN-4OUT expansion unit is housed in a 4-module box for DIN rail. It has four configurable analog inputs which can be connected to the following devices:

- temperature sensors for common areas;
- alarm or anomaly contacts;
- switches;
- buttons;
- bathroom emergency pull cords;
- overflow sensors;
- energy meters.

It also has four relay outputs with voltage-free contacts for 230Vac, 4(2)A loads for managing devices connected to the relative inputs (thermostats, etc.) and ON/OFF or timed activation via computer. Connection to the UGT-IP control unit and other expansion and monitoring units via RJ12 connectors also with necessary 12Vdc power supply. Alternatively, may be supplied directly by specific 12Vdc, 3.5A power supply unit. Dimensions 70x100x62 mm. Weight 0.3 Kg.